





# AQUAPURA BOOSTER A COMPACT EQUIPMENT FOR HOT WATER

PORTUGUESE MANUFACTURING

The Booster is a highly efficient water-water heat pump for the prodution of domestic hot water that works in combination with a district heating system or domestic heat network.

Both in district heating systems and heat networks, the temperature offered is normally insufficient for the production of domestic hot water. However, the Aquapura Booster water-to-water heat pump uses low-temperature water as a heat source for the production of domestic hot water up to 60°C.

Low temperature systems are becoming increasingly important in the house market. In such a system, a centrally located heat pump provides low-temperature water up to 35°C to multiple apartments or single houses. The high efficiency and limited heat loss mean that these types of systems achieve a very favorable energy rating in collective or single housing projects. The low-temperature water can be used directly for the radiant floor of the residential units.









#### + PERFORMANCE

The Booster has a high coefficient of performance (COP), meaning that it is extremely efficient at converting energy into heat. This translates into lower energy bills and a reduced carbon footprint for homeowners.



### + HOUSE COOLING & QUIET OPERATION

When integrated with the house heating system, this product has the added benefit of cooling the house during the hot summer months. The Booster produces minimal noise during opera-

tion, ensuring that it won't disturb the peace and quiet of your home.



#### + INSTALLATION

The Booster is designed with horizontal transportation and easy installation in mind, making it a convenient and hassle-free option for households of all sizes.

![](_page_2_Picture_12.jpeg)

#### + PV AND SG READY

With PV Smart Grid Ready, the ENERGIE Solar System absorbs the extra power generated by PV Panels, Wind Energy or Small Hydro storing, what would be lost energy, into the water, enabling you to save even more.

Storage Water Heater. 2. Block
Photovoltaic Panels. 4. Inverter.

## BOOST YOUR SAVINGS AND COMFORT

With its innovative technology, the Booster can extract heat from the central heating circuit and use it to heat water in a storage tank. This process is reliable and efficient, making it an ideal solution for homes of all sizes, including apartment buildings.

By using a Booster, households can save money on their energy bills and reduce their carbon footprint. With its flexibility and versatility, the Booster is an excellent choice for anyone looking to improve the efficiency of their water heating. The unit can be conveniently controlled from

![](_page_3_Figure_3.jpeg)

the comfort of your home, thanks to its intuitive user-friendly control panel. With the ability to access all main operational modes, functions, set points, and information from the control panel, you can easily customize your heating settings to suit your preferences. The Booster offers several operational modes, including AUTO, ECO, BOOST, BACKUP and HOLIDAY, making it a flexible and adaptable heating solution for any situation.

Professionals prefer this model due to its effortless installation procedure. It's lightweight and easily manoeuvrable, making it easy to transport and install in any type of housing.

This cylinder is made entirely of stainless steel, which eliminates the issue of corrosion. As a result, there is no need for an anode, which eliminates maintenance requirements and constraints. This makes the product a more convenient and cost-effective option for those who want to avoid the hassle of frequent maintenance.

# ELECTRONIC CONTROLLER DOMESTIC HOT WATER

PRODUCTION

![](_page_3_Picture_9.jpeg)

1. Compressor 2. Electrical Heater 3. Disinfect 4. Solar function 5. Alarm

![](_page_3_Picture_11.jpeg)

| TECHNICAL DATA                                    |              | BOOSTER 1201                       | BOOSTER 2001    | BOOSTER 300I |  |
|---------------------------------------------------|--------------|------------------------------------|-----------------|--------------|--|
| Type of equipment                                 | -            | Water/water heat pump for DHW      |                 |              |  |
| DHW capacity                                      | L            | 120                                | 200             | 270          |  |
| Empty weight                                      | Kg           | 41                                 | 58              | 98           |  |
| Dimensions (height/ø)                             | mm           | 1400/530                           | 1667/580        | 1968/580     |  |
| Storage water heater material                     | -            |                                    | Stainless steel |              |  |
| Max running temperature cylinder                  | °C           |                                    | 80              |              |  |
| Max working pressure cylinder                     | bar          |                                    | 7               |              |  |
| Heat loss                                         | kWh/24h      | 0,95                               | 0,99            | 1,01         |  |
| Protection index                                  | -            |                                    | IPX1            |              |  |
| Power supply                                      | -            | 220-240 Vac / Single-Phase / 50 Hz |                 |              |  |
| Absorbed power (med / max)                        | W            | 280/350                            | 350/650         | 350/650      |  |
| Absorbed power electrical support                 | W            | 1500                               | 1500            | 1500         |  |
| Thermal power supplied Heat Pump (med / max)      | $\mathbb{W}$ | 1470 / 1800                        | 1800 / 2750     | 1800 / 2750  |  |
| Max running current (Heat Pump + Electrical Heate | r) A         | 1,5+6,5                            | 2,9 + 6,8       | 2,9 + 6,8    |  |
| Max DHW temperature (Heat Pump)                   | °C           |                                    | 60              |              |  |
| Max DHW temperature (Backup)                      | °C           |                                    | 75              |              |  |
| Refrigerant                                       | -/Kg         |                                    | R134a / 1.2     |              |  |
| Load profile                                      | -            | Μ                                  | L               | XL           |  |
| COP 1)/2)                                         |              | 4,0/4,3                            | 5,4/ 6,2        | 5,4 / 6,4    |  |
| Heating time <sup>1)/2)</sup>                     |              | 3:55/3:32                          | 3:15/3:03       | 4:38/4:21    |  |
| Amount of useful water 40°C <sup>1) / 2)</sup>    |              | 138/138                            | 260/262         | 332/335      |  |
| Energy efficiency class <sup>1)/2)</sup>          |              | A+++/A+++                          | A+++/A+++       | A++/A+++     |  |
| Energy efficiency <sup>1) / 2)</sup>              |              | 166/180                            | 226/280         | 226 / 265    |  |
| Annual electricity consumption <sup>1)/2)</sup>   |              | 310/285                            | 453/366         | 742 / 632    |  |
| Sound power level indoor <sup>3)</sup>            |              |                                    | 45              |              |  |

<sup>1</sup>) Heat source at 25° and DHW temperature from 10°C-53°C, according to EN16147 and regulamentation (EU) N°812/2013 | <sup>2</sup>) Heat source at 35° and DHW temperature from 10°C-53°C, according to EN16147 and regulamentation (EU) N°812/2013 | <sup>3</sup>) According with EN12102

| DIMENSIONS mm | Ø Pol.   |                         | 1201 | 2001 | 3001 |
|---------------|----------|-------------------------|------|------|------|
| A             | -        |                         | 1400 | 1667 | 1968 |
| В             | G ¾" M   | Cold water inlet        | -    | 131  | 131  |
| С             | G 1⁄2" F | Recirculation           | -    | -    | 840  |
| D             | G 1⁄2" F | PT Valve                | -    | 905  | 1205 |
| E             | G ¾" M   | Hot water outlet        | -    | 1030 | 1325 |
| F             |          |                         | Ø530 | Ø580 | Ø580 |
| G             | G ¾" M   | Heat source connections | 3/4" | 3/4" | 3/4" |
| Н             |          |                         | 720  |      |      |
|               |          |                         | 826  |      |      |
| J             |          |                         | 220  |      |      |
| K             |          |                         | 100  |      |      |
| L             | G ¾" M   | Cold water inlet        |      |      |      |
| Μ             | G ¾" M   | Hot water outlet        |      |      |      |

#### Equipment: Aquapura Booster

![](_page_4_Figure_4.jpeg)

![](_page_4_Figure_5.jpeg)

![](_page_4_Figure_6.jpeg)

![](_page_4_Figure_7.jpeg)

Booster 120i

Booster 200i

Booster 300i

This flyer has been created for information purposes only and does not constitute a contractual offer for ENERGIE EST Lda. A ENERGIE EST Lda. has compiled the contents of this flyer to the best of its knowledge. No express or implied guarantee is given regarding the completeness, accuracy, reliability or fitness for a particular purpose of its content and the products and services it presents. Specifications are subject to change without notice. ENERGIE EST Lda. explicitly rejects any direct or indirect damages, in its broadest sense, resulting from or related to the use and/or interpretation of this flyer. R0V0/2024

![](_page_5_Picture_1.jpeg)

Project co-financed by:

![](_page_5_Picture_3.jpeg)

![](_page_5_Picture_4.jpeg)

![](_page_5_Picture_5.jpeg)

![](_page_5_Picture_6.jpeg)

Zona Industrial de Laúndos Lote 48, 4570-311 Laúndos Póvoa de Varzim, Portugal EMAIL energie@energie.pt SITE www.energie.pt

Follow us on: ENERGIE PORTUGAL Authorized dealer