



AQUAPURA INVERTER HT

HEATING & COOLING +
DOMESTIC HOT
WATER



**AEROTHERMY
HEAT PUMP.**
LATEST GENERATION
OF HEAT PUMP
WITH NEW R290
NATURAL
REFRIGERANT.



THE LATEST GENERATION OF AIR TO WATER HEAT PUMPS

WITH NATURAL REFRIGERANT R290

ENERGIE.PT



Uses a natural refrigerant with a lower global warming potential.



Operates with minimal noise, nearly imperceptible from just a few meters away.



The connections are entirely hydraulic, with no fluorinated gases involved.



High performance in all applications: heating, cooling, and domestic hot water (DHW) production.



The Aquapura inverter features an ABS polymer-coated exterior, specifically designed for enhanced protection against corrosion.



This Aquapura Inverter can achieve temperatures above 70°C, making it an ideal solution for boiler replacement.



With an A+++ efficiency class and a SCOP coefficient near 5, the unit offers one of the highest efficiency levels on the market.



INTUITIVE TOUCH CONTROL



HEATING & COOLING +
PRODUCTION OF DHW

1. ON/OFF
2. Operating mode
3. Temperature
4. Setpoint
5. Keyboard blocking
6. Menu



COMPATIBLE WITH THE THERMOBOX RANGE

The INVERTER HT is fully compatible with the Aquapura THERMOBOX range! These models, part of ENERGIE's ALL-IN-ONE line, consist of just two units—an outdoor and an indoor unit—both 100% hydraulic. All components are housed within the indoor unit, offering a versatile and compact solution. Perfect for multi-family homes and residential buildings.



MAXIMUM
RETURN ON
INVESTMENT

NEW CLIMATE SOLUTION

All that is needed is to have a substructure of water terminals, namely radiators, invisible radiant heating or fan coils, to be able to enjoy this new solution for Heating & Cooling and Domestic Hot Water production.

FUNCTIONING

PRINCIPLE

ENERGIE.PT

There is a cooling liquid that is pumped to an outdoor heat exchanger (evaporator). Here the liquid, with the help of a fan, absorbs the energy from the atmosphere to the temperature differential obtained outdoors. During this process, the liquid changes to a gaseous state. The gaseous state is sucked in by the mechanical part of the system, the compressor. Here it is compressed, the pressure goes up and consequently the liquid temperature increases. After this, the liquid travels to a second inside heat exchanger (condenser) and transfers heat to the water in the cylinder. The fluid goes into liquid state by cooling down. The liquid pressure is reduced due to a strangulation that happens in the expansion valve and the process starts again.

INVERTER HEAT PUMPS

STAND OUT FOR THEIR HIGH PERFORMANCE

Heat pumps are prepared for heating and cooling as well as domestic water heating. These solutions stand out for their high energy efficiency, which makes them capable of achieving an energy rating up to A+++ for heating. They also stand out for their ability to integrate with other heating systems and easy installation.

HIGH LEVEL OF EFFICIENCY

DOMESTIC HOT WATER PRODUCTION

The heat from the environment is indirect solar energy, stored in water, air and soil. The heat pump will extract heat precisely from these heat sources for later use in your home's climate. Air/Water heat pumps with high energy efficiency INVERTER technology are a modern, efficient and clean solution that guarantees the comfort of your home, always respecting the environment.

It's a smart way to use nature's resources to improve your quality of life. By adopting one of these solutions, you will be making a serious commitment to the issue of reducing harmful emissions to our atmosphere, thus contributing to the planet's natural balance. The Air/Water heat pumps with INVERTER technology were developed to meet the needs of both domestic and industrial use, for climatization (heating and cooling) and Domestic Hot Water solutions (DHW).

CONSUMPTION OF PRIMARY ENERGY





CHART OF ENERGY CONSUMPTION

KEY FEATURES

- The highest efficiency on the market
- Heating and/or Cooling
- Reduced maintenance and low operating noise
- Operation at outdoor temperatures down to -25°C
- Manufactured with a corrosion-resistant ABS coating
- Domestic Hot Water Function

DC INVERTER TECHNOLOGY



DC INVERTER technology is different from any other technology existing on the market because it has a compressor with the capacity to vary the operating frequency, meeting the exact needs of climatization comfort at home. This achieves greater savings in energy consumption.




TECHNICAL DATA (Outdoor Unit)			AQUAPURA 8HT	AQUAPURA 12HT	AQUAPURA 14HT	AQUAPURA 14HT-T	AQUAPURA 22HT-T
Power Supply			230V~/50Hz	230V~/50Hz	230V~/50Hz	400V~/3F+N/50Hz	400V~/3F+N/50Hz
Power Supplied	Heating (Nom./Max)	kW	8,95-10,30	12,30-14,50	14,21-16,70	14,21-16,70	22,00-25,47
	Cooling (Nom./Max)	kW	5,98-8,51	10,14-11,60	9,71-11,61	9,71-11,61	16,04-17,16
Power consumed	Heating (Nom./Max)	kW	1,86-3,00	2,50-5,10	2,83-5,30	2,83-5,30	4,94-9,01
	Cooling (Nom./Max)	kW	1,64-3,00	2,61-5,10	2,45-5,30	2,45-5,30	4,44-9,01
COP ¹	Nominal		4,8	4,92	5,02	5,02	4,45
ERR ²	Nominal		3,65	3,88	3,96	3,96	3,61
Energy efficiency class at 35°C ³			A+++	A+++	A+++	A+++	A+++
SCOP Seasonal efficiency at 35°C ³			5,00	4,82	4,90	4,90	4,91
Energy efficiency class at 55°C ³			A++	A++	A++	A++	A++
SCOP Seasonal efficiency at 55°C ³			3,71	3,53	3,76	3,76	3,70
Maximum consumption power	kW		3,0	5,1	5,3	5,3	9,1
Maximum consumption current	A		13,5	22	24,5	10,5	15,8
Refrigerant (R290) / CO ₂ Eq.	kg/Ton		0,5 / 0,0015	0,8 / 0,0020	0,85 / 0,0025	0,85 / 0,0025	1,3 / 0,004
Compresor			DC Inverter	DC Inverter	DC Inverter	DC Inverter	DC Inverter
Sound Pressure at 1m	dB(A)		46	46	43	44	44
Sound power	dB		60	51	57	58	62
Hydraulic Connections Diameter	Pol.		1"	1"	1"	1"	1"
Circulator			Integrated	Integrated	Integrated	Integrated	Integrated
Minimum water flow	m ³ /h		1	1,4	1,6	1,6	2,9
Hydraulic circuit load loss	kPa		20	15	30	30	45
Dimensions	(HxWxD)		795x1167x445	790x1167x420	928x1287x500	928x1287x500	1329x1247x540
Weight	kg		80	120	160	160	202

¹ Air temperature (DB/WB) 7°C/6°C; Water temperature (inlet/outlet) 30°C/35°C | ² Air temperature (DB/WB) 35°C/24°C; Water temperature (inlet/outlet) 12°C/7°C | ³ In compliance with EN14825 and Delegated Regulation (EU) No. 812/2013

TECHNICAL DATA THERMOBOX DHW (Indoor Unit)			INVERTER 8HT		INVERTER 12HT			INVERTER 14HT 14HT-T		INVERTER 22HT-T
			160L	200L	160L	200L	270L	200L	270L	270L
Heating Time ($\Delta t=35^{\circ}\text{C}$)	hh:mm		00:44	00:55	00:32	00:40	00:54	00:34	00:47	00:31
COP / SCOP ⁴			3,31	3,32	3,34	3,36	3,38	3,32	3,36	3,30
Consumption Profile ⁴			L	L	L	L	XL	L	XL	XL
Energy-Efficiency ⁴	%		138	139	139	141	141	139	140	137
Quantity of Hot Water Available (40°C) ⁴	L		205	257	205	257	332	258	332	338
Energy Class ⁴			A+	A+	A+	A+	A+	A+	A+	A+
DHW Maximum Temperature AQS	°C		60	60	60	60	60	60	60	60



⁴ A14/W10-54, in compliance with EN16147 and Delegated Regulation (EU) No. 812/2013

Equipment: **INVERTER 8HT | 12HT | 14HT | 14HT-T**



1. Power supply
2. Communication
3. Water outlet
4. Water return

Equipment: **INVERTER 22HT-T**



DIMENSIONS mm	8HT	12HT	14HT 14HT-T	22HT-T
A	1167	1167	1287	1247
B	795	790	928	1329
C	229	239	238	155
D	339	331	363	985
E	830	830	975	800
F	445	420	500	540
G	428	400	458	503
H	166	167	125	216
3	1"	1"	1"	1"
4	1"	1"	1"	1"

This flyer has been created for information purposes only and does not constitute a contractual offer for ENERGIE EST Lda. ENERGIE EST Lda. has compiled the contents of this flyer to the best of its knowledge. No express or implied guarantee is given regarding the completeness, accuracy, reliability or fitness for a particular purpose of its content and the products and services it presents. Specifications are subject to change without notice. ENERGIE EST Lda. explicitly rejects any direct or indirect damages, in its broadest sense, resulting from or related to the use and/or interpretation of this flyer. R3V0/2024



Project co-financed by:



Zona Industrial de Laúndos
Lote 48, 4570-311 Laúndos
Póvoa de Varzim, Portugal
EMAIL energie@energie.pt
SITE www.energie.pt

Follow us on:
ENERGIE PORTUGAL
   

Authorized dealer